

Dura Gloss

DESCRIPTION

Once dry, this true commercial grade floor finish can be damp mopped or even scrubbed with a detergent solution, without removing the finish or even affecting its gloss. Modern acrylic polymers crosslink to form a high gloss finish that resists scuffing, stains and black marks and protects the floor from traffic.

For use on vinyl, vinyl asbestos, asphalt tile, rubber, linoleum, tile and other floors.

HOW TO USE

May be applied over other hard, non-wax finishes. But for assured results, the old brand of polish should be removed, and the new finish applied to a clean, dry floor.

1. Apply finish in straight, even strokes that will cover fully, but not so liberally as to run into spots.
2. Allow to dry completely. Do not re-work finish while it is drying.
3. When dry, an additional coat, or coats, may be applied if needed. Apply each succeeding coat a little less liberally than the previous one.

FUTURE CARE: Regular dry mopping, damp mopping, and burnishing will extend durability. Use a compatible restorer when high speed polishing. Worn or dirty areas may be cleaned and spot coated without re-coating the entire floor.

SPECIFICATIONS

APPEARANCE	Milky liquid
FRAGRANCE	Characteristic
SPECIFIC GRAVITY	1.020 ± 0.005
DENSITY	8.51 ± 0.05 lb/gal
BOILING POINT	Near 212OF
pH.....	8.5 ± 0.5
FLASH POINT	None to boiling OF
STABILITY	One year minimum

BLIND INDUSTRIES AND
SERVICES OF MARYLAND
3345 WASHINGTON BLVD
BALTIMORE, MD 21227
(888) 322-4567