

# PRODUCT INFORMATION SHEET

## REBOUND

**Description:** REBOUND is a high or low speed maintainer for acrylic and acrylic/urethane floor finishes. It can be used as a mop on product or spray buff. REBOUND not only gives a high gloss and wet look, but is also an excellent cleaner. REBOUND may be used in automatic scrubbers or may be used with a low or high speed machine when top scrubbing the floor. It is formulated to use at 4-6 ounces per gallon of water.

**Benefits:**

- Increases slip resistance
- High dilution factor for economy use
- Restores gloss and appearance without finish build-up
- Does not soften finish surface
- Burnishes out quickly for productivity
- Excellent cleaner

**Specifications:**

|                     |   |
|---------------------|---|
| Appearance          | Clear liquid  |
| Color               | Pink  |
| Odor                | Peppermint  |
| Specific Gravity    | 1.01 ± 0.03 @ 20°C  |
| Flash Point         | None  |
| pH: as is           | 3.0 ± 0.5   |
| pH: 1:              | ±   |
| Use Dilution        | 4 oz. - 6 oz. per gallon mop on<br>32 oz. per gallon spray on |
| Storage Stability   | One year in sealed container                                  |
| Protective Clothing | None normally required  |

**Comments:** REBOUND contains no waxes to soften the surface and cause potential slip problems.

**Packed:** 1.5 plastic bottles (four per case)

**Date:** December 5, 1997

This sheet is not an M.S.D.S., nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described hereon is for use only by trained professional cleaning personnel.